



Optical Assemblies (Pigtails/Patch Cords)

Optical cable assemblies (pigtail/patch cord) are the base passive products in optical communication system. CISFIBER Infra Solution's provides a broad variety of cable assemblies including SC, FC, LC with Ultra-polished, Angle-polished (APC) or other polish requirement for use in FTTx, telecommunications, data communications and CATV applications.

Fiber Optic Cabling: Patch Cords and Pigtails



All materials are RoHS Compliant



ST connector types are available on request.

Performance Specification:

Connectors comply to IEC 61754-20 , IEC 61754-4 & IEC 61754-13 respectively.

Products comply to ISO/IEC 11801

Multimode	Fiber type	Max . Attenuation (dB)	Min. Return Loss (dB)
LC , SC , FC (PC)	OM1,OM2	0.30	20
FC (PC)	OM3,OM4	0.30	20
LC, SC (PC)	OM3,OM4	0.30	35

Single mode	Fiber type	Max . Attenuation (dB)	Min. Return Loss (dB)
LC , SC , FC (PC)	OS1/OS2	0.30	45
LC , SC (UPC)	OS1/OS2	0.30	50
LC, SC, FC (APC)	OS1/OS2	0.30	60

IL/RL are measured against reference connectors

Typical Characteristics:

Item	Specification
Fiber Cable retention	$\varnothing > 1.8$ mm; Max 50N (For jacketed cable)
Mating Durability	500 cycles
Operating temperature	-20°C to +60°C
Storage temperature	-20°C to +60°C

Endface Geometry Specification:


Parameter	Specification	
	UPC	APC
Endface	UPC	APC
Radius of curvature	$5\text{mm} \leq R \leq 30\text{mm}$	$5\text{mm} \leq R \leq 12\text{mm}$
Apex Offset	$< 50\mu\text{m}$	$< 50\mu\text{m}$
Spherical height	-100nm to +100nm	-100nm to +100nm
Polish Angle	NA	8° (+/-0.3)

APPLICATIONS

- Optical distribution
- Wide Network Area
- CATV
- Passive Optical Network
- Local Area Network
- FTTx application

ORDERING GUIDE

1. Pigtailed 900micron & 2.0 - 3.0mm Jacketed



900 micron Pigtailed



2.0mm & 3.0mm Pigtailed

<u>PT</u>											
Product Family		Connector 1		Cable Type		Fiber Type		Jacket Material		Length	
Type	Catalog Code	Type	Catalog Code	Cable Construction	Catalog Code	Fiber Type	Catalog Code	Jacket Material	Catalog Code	Length	UoM
Pigtail	PT	SC/PC	SCP	900μ Buffer	9B	SM OS1/OS2 G652D	2D	LSZH	LS	XXXM	M
		SC/APC*	SCA	2.0mm	2S	SM G657A1	A1	PVC	PV	DXXM	M
		LC/PC	LCP	3.0mm	3S	SM G657A2	A2				
		LC/APC*	LCA			SM G657B1	B1				
		FC/PC	FCP			SM G657B2	B2				
		FC/APC*	FCA			OM1	M1				
		ST/PC	STP			OM2	M2				
						OM3	M3				
				OM4	M4						

*APC version only available with SM Fiber only

*Use DXX for Decimal Lengths

